

# SNO-L6013RP



## 2 Megapixel, IP outdoor camera with IR Led

- local video and image storage on SD card
- Multi-Crop Streaming with user management
- Up to 70% less bandwidth utilization, with improved Samsung processing

## Summary

In a crowded professional security camera market place where there is no shortage of manufacturers competing for the attention of users and installers, Samsung Techwin has yet again demonstrated its determination to retain its market leading position and stand out from the crowd with the launch of its high definition WiseNet Lite series. The bullet cameras and domes in the new WiseNet Lite series have been introduced to provide Samsung Techwin customers with keenly priced alternatives to the highly acclaimed, feature rich. The 1.3MP and 2MP Full HD WiseNet Lite models share many of the features built into the WiseNetIII range, including motion detection, privacy masking zones, audio support, PoE and a memory slot. They also feature LDC (Lens Distortion Correction), which compensates for the image distortion that can occur with wide angle lenses. Samsung Techwin has also equipped the WiseNet Lite cameras and domes with a Hallway view function for the monitoring of narrow vertical areas such as corridors, tunnels and aisles. It enables the camera to capture images with different aspect ratio that works effectively in tall and narrow spaces with the added bonus of minimizing bandwidth and video storage requirements.

# SNO-L6013RP

## Technical Specifications

<b>Image Sensor</b>	1/2.9" CMOS Full HD
<b>Scanning System</b>	Progressive
<b>Col/B</b>	On/Off/Auto, IR-cut filter removable (ICR)
<b>Max. Framerate H.264</b>	25/30 fps @ all resolutions
<b>Sensitivity Colour</b>	0.15 lux @ F1.8
<b>Sensitivity B/W</b>	0 Lux LED IR on
<b>Max. IR Distance</b>	10/20 m (according to scene reflexion)
<b>Lens Drive Type</b>	DC Auto Iris
<b>S/N Ratio</b>	50 dB
<b>Lens Focal Length</b>	3.6 mm
<b>Horizontal Viewing Angle</b>	86.5°
<b>Minimum Object Distance</b>	0.5 m
<b>Number of Privacy Zones</b>	6 rectangle
<b>Focus Adjustment</b>	Manual
<b>Pan Range</b>	0° ~ 350°
<b>Tilt Range</b>	0° - 67°
<b>Rotate</b>	0° - 355°
<b>Digital Noise Reduction</b>	SSNR (Off/On)
<b>Intelligent Video Analytics</b>	Motion detection, Tampering
<b>BLC Back Light</b>	On/Off
<b>Camera ID</b>	16 character
<b>White Balance</b>	ATW, Manual, AWC, Indoor, Outdoor
<b>Client OS</b>	Windows® XP / VISTA / 7 / 8 / 8.1, MAC OS® X 10.7 ~ 10.10
<b>Web Browser</b>	MS Internet Explorer 6.0 (or higher), Firefox, Google Chrome, Safari
<b>Video Management Software</b>	SmartViewer 4.0
<b>Video Compression</b>	H.264, MJPEG, Single/ Dual Stream
<b>Audio Compression</b>	G.711 u-law, G.726 (16Kbps, 24Kbps, 32Kbps, 40Kbps)
<b>Network Streaming</b>	TCP, UDP (Unicast, Multicast)
<b>Network Interface</b>	1x 10/100 Base T/TX (RJ-45)
<b>Security</b>	HTTPS(SSL) Login Authentication Digest Login Authentication, IP Address Filtering

**SNO-L6013RP****Technical Specifications**

<b>Alarm Event</b>	File upload via FTP and E-mail, Local storage recording at event, Notification via E-mail
<b>SD memory</b>	supports up to 32 GB capacity of micro SD/SDHC memory
<b>System Compatibility</b>	ONVIF Profile G, ONVIF Profile S
<b>Material</b>	Plastic
<b>Protection Rating</b>	IP66
<b>Operating Temperature</b>	-30°C ~ +55°C
<b>Humidity</b>	less than 90%, non condensing
<b>Supply Voltage</b>	PoE (IEEE 802.3af)
<b>Power Consumption (W)</b>	5.7
<b>Weight</b>	0.25 kg - 0.55 lbs
<b>Dimensions</b>	∅ 58.6 x 165.2 mm - 2.31 x 6.5 In