

IPC3611SR3-(P)F28(36)(60) 1.3MP Network IR Fixed Dome Camera



Key Features

Optics

- Day/night functionality
- Optical glass window with higher light transmittance
- IR anti-reflection window to increase the infrared transmittance
- Up to 30 m (98 ft) IR distance
- 3D noise reduction

Compression

- H.264/MJPEG
- Dual streams

Network

- ONVIF Conformance

Structure

- Support PoE power supply (optional)
- Wide temperature range: -30°C to 60°C (-22°F to 140°F)
- Wide voltage range of $\pm 25\%$
- 4 KV surge protection designed for network interface
- IP66-rated

Specifications

| | IPC3611SR3-F28(36)(60) | IPC3611SR3-PF28(36)(60) |
|-------------------------|---|--------------------------------|
| Camera | | |
| Sensor | 1/3", 1.3 Megapixel, progressive scan, CMOS | |
| Lens | 2.8mm@F1.8(3.6mm, 6mm optional); Angle of view(H): 99.1° (76.7° / 46.9°) | |
| Shutter | Auto/Manual, 1/6~1/8000 s | |
| Day/Night | IR-cut filter with auto switch (ICR) | |
| IR | 30m (98 ft) IR range | |
| AWB(Auto white balance) | Auto/manual | |
| Gain Control | Auto/manual | |
| WDR | Digital | |
| Noise Reduction | 2D/3D | |
| Video | | |
| Max. Resolution | 1280×960 | |
| Video Compression | H.264/MJPEG | |
| Frame Rate | 960P (1280×960): Max. 30 fps; 720P (1280×720): Max. 30 fps; D1 (720×576): Max. 25 fps | |
| Video Streaming | Dual | |
| OSD | Up to 8 OSDs | |
| Motion Detection | Up to 2 areas | |
| Privacy Mask | Up to 4 areas | |
| Network | | |
| Protocols | IPv4,IGMP,ICMP,ARP,TCP,UDP,DHCP,RTP,RTSP,Qos,DNS,DDNS,NTP,FTP,UPnP,HTTP | |
| Compatible Integration | ONVIF | |
| Interface | | |
| Network | 10M/100M Base-TX Ethernet | |
| General | | |
| Power Supply | 12 V DC | 12 V DC, or PoE (IEEE802.3 af) |
| | Power consumption: 3.5 W (with IR on: extra 2 W) | |
| Dimensions (Ø x H) | Ø126 x 94 mm (Ø5.0" x 3.7") | |
| Weight | 0.33 kg (0.73 lb) | |
| Working Environment | -30°C ~ +60°C (-22°F ~ 140°F), Humidity ≤ 90% RH(non-condensing) | |

Dimensions

